



**OS-2140DZ** 203 dpi  
**OS-214plus** 203 dpi



**Desktop Label Printer | Outstanding Series**



**Trusted Dependability, Quality Assured, Exceptional Value**

**STREAMLINED FEATURES**

- Competitive Emulations
- Durable and Easy Maintenance
- Compact Size
- Built-in Interfaces
- Universal Switching Power Supply

**INDUSTRY VERTICALS**

- Healthcare
- Retail
- Transportation & Logistics
- Office Administration
- Education & Libraries
- Hospitality

**INDUSTRY APPLICATIONS**

- Laboratory Labeling
- Shelf Labeling
- Product Labeling
- File Folder Labeling
- Layaway Marking
- Price Markdowns
- Asset Tracking

PRINTER MODEL		OS-2140DZ	OS-214plus
<b>PRINT SPECIFICATIONS</b>			
<b>Printing Method</b>		Direct Thermal	Direct Thermal/Thermal Transfer
<b>Print Resolution</b>		203 dpi (8 dots/mm)	
<b>Printing Speed</b>		Up to 4 ips (102mm/s)	Up to 3 ips (76mm/s)
<b>Max. Print Area</b>		4.16" (105mm) W x 100" (2540mm) L	4.16" (105mm) W x 43" (1092mm) L
<b>MEDIA SPECIFICATIONS</b>			
<b>Sensor Type</b>		Reflective used for both Gap & I-mark	
<b>Media Type</b>		Roll and Fanfold	
<b>Media Size</b>	<b>Width</b>	1" to 4.33" (25.4mm to 110mm)	
	<b>Thickness</b>	0.0025"-0.01" (0.0635-0.254mm)	
	<b>Roll Specs</b>	Max O.D.: 4.3" (109mm) / I.D.: 1" (25.4mm)	
<b>Ribbon (TT only)</b>		Width: 1"-4", Max O.D.: 1.45" (37mm), Paper Core: 0.5" (13mm) with notch, CSO	
<b>FONT / SYMBOLOGIES</b>			
<b>Internal Fonts</b>		5 alpha-numeric fonts from 0.049"-0.23 H (1.25mm-6.0mm), expandable up to 24x24	
<b>Barcode Symbologies</b>	<b>Linear</b>	PPLZ: Code 39 (standard/with checksum digit), Code 93 Interleaved 2 of 5 (standard/with checksum digit/with human readable check digit), EAN-8, EAN-13, UPC-A, UPC-E, Postnet, Codabar, Code 128 subset A/B/C, Code 128 Auto, UPC/EAN-Extension, Plessey, Industrial 2 of 5, Standard 2 of 5, Logmars, MSI, Code 11, GS1 DataBar	PPLA: Code 39, Code 93, Code 128/subset A/B/C, Codabar, Interleaved 2 of 5, UPC A/E/2/5 add-on, EAN-13/8, UCC/EAN 128, Postnet, Plessey, Interleaved 2 of 5, Interleaved 2 of 5 with a modulo 10 checksum, Interleaved 2 of 5 with a modulo 10 checksum and shipping bearer bars, Code 128, UCC/EAN Code 128 Random Weight, HBIC, Telepen, FIM  PPLB: Code 39, Code 93, Code 128/ subset A,B,C, Codabar, Interleaved 2 of 5, Interleaved 2 of 5 with check sum digit, Interleaved 2 of 5 with human readable check digit, Matrix 2 of 5, UPC A/E 2 and 5 add-on, EAN-8/13, Code 128UCC, UCC/EAN, Postnet
	<b>2-D</b>	PPLZ: MaxiCode, PDF417, Data Matrix, QR code, Composite codes	PPLA: PDF-417, MaxiCode, Data Matrix, QR Code, Composite codes  PPLB: MaxiCode, PDF-417, QR Code, Composite codes
<b>COMMUNICATION INTERFACE</b>			
<b>Interface Options</b>		RS-232, USB	Parallel, RS-232, USB
<b>MEMORY</b>			
<b>Memory</b>		Flash ROM: 4MB, RAM: 8MB	
<b>OPERATING CHARACTERISTICS</b>			
<b>Power Requirements</b>		AC Adapter Input voltage: 100V~240V, Frequency: 50/60Hz, Output voltage: 24VDC, 2.4A	
<b>Environment</b>	<b>Operating</b>	40°~100°F (4°~38°C) / 0%-90% non-condensing	
	<b>Storage</b>	-4°~122°F (-20°~50°C)	
<b>Regulatory Approvals</b>		CE, cTUVus, FCC, CCC, RoHS	CE, FCC, UL, CUL, CCC, RoHS, Energy Star Rated
<b>Dimensions</b>		7.32" (186mm) W x 10.94" (278mm) D x 6.5" (165mm) H	
<b>Weight</b>		4.4 lbs (2.0Kg)	
<b>OPTIONS</b>			
<b>Printer Languages</b>		PPLZ	PPLA / PPLB
<b>Optional Accessories</b>		Cutter, Media Roll Unwind, RTC Card	
<b>Other Features</b>		Printer Utility, Font Utility, Windows Driver	